




DIN 911

~ISO 2936

Norma stažena



BN 1169

Klíče pro šrouby s vnitřním šestihranem

A: metrický; B: UNC/UNF

Ocel tepelně zušlechťeno

černěno

- ~UNI 6753

typ B UNC/UNF: není obsaženo v DIN 911, 30: dle ISO 2936

Article#	Customer Article#	s	±	L ₁	L ₂	Typ
1380869		0,7	0,011 / -0,002	32	6	A
1380931		0,9	-0,011 / -0,024	32	10	A
1380478		1,3	-0,030 / -0,056	40	12	A
1380605		1,5	0 / -0,025	45	14	A
1380613		2	0 / -0,04	50	16	A
1411047		2,5	0 / -0,04	56	18	A
1411055		3	0 / -0,04	63	20	A
1411063		4	0 / -0,048	70	25	A
1411071		5	0 / -0,048	80	28	A
1411098		6	0 / -0,048	90	32	A
1411101		7	0 / -0,058	95	34	A
1411128		8	0 / -0,058	100	36	A
1411136		9	0 / -0,058	112	40	A
1411144		10	0 / -0,058	112	40	A
1411152		12	0 / -0,110	125	45	A
1411160		14	0 / -0,11	140	56	A
1411179		17	0 / -0,11	160	63	A
1411187		19	0 / -0,13	180	70	A
1411195		22	0 / -0,13	200	80	A
1411209		24	0 / -0,13	224	90	A
1411217		27	0 / -0,13	250	100	A
1411225		30	0 / -0,16	280	112	A
1411233		32	0 / -0,16	315	125	A
1411241		36	0 / -0,16	355	140	A
1411268		0,05"		42	13,5	B
1411276		1/16"		44	13,5	B

typ B UNC/UNF: není obsaženo v DIN 911, 30: dle ISO 2936

Article#	Customer Article#	s	±	L1	L2	Typ
1411284		5/64"		47	15,5	B
1411292		3/32"		51	16,5	B
1411306		1/8"		57	19	B
1411314		5/32"		64	21,5	B
1411322		3/16"		70	24	B
1411330		7/32"		76	26	B
1411349		1/4"		83	29	B
1411357		5/16"		95	32	B
1411365		3/8"		108	35	B
1411373		1/2"		133	41	B
1411381		9/16"		146	45	B
1411403		5/8"		159	48	B
1411411		3/4"		184	54	B
1411438		1"		237	69	B