


**DIN 127 A**

Norma stažena

**BN 760****Pružné podložky**

se zahnutými konci

Pružinová ocel

mechanicky pozinkováno modrý chromát

- ~UNI 1751 A
- ~CSN 021741



Pro nové konstrukce doporučujeme DIN 128 A (zvlněné pružné pojistné podložky): BN 768 / BN 769 / BN 770

Article#	Customer Article#		d ₁ min.	d ₁ max.	d ₂ max.	s
1275178		M3	3,1	3,4	6,2	0,8
1436910		M3,5	3,6	3,9	6,7	0,8
1275194		M4	4,1	4,4	7,6	0,9
1275208		M5	5,1	5,4	9,2	1,2
1275216		M6	6,1	6,5	11,8	1,6
1275224		M8	8,1	8,5	14,8	2
1275232		M10	10,2	10,7	18,1	2,2
1275240		M12	12,2	12,7	21,1	2,5
1436937		M14	14,2	14,7	24,1	3
1275259		M16	16,2	17	27,4	3,5
1436945		M18	18,2	19	29,4	3,5
1275267		M20	20,2	21,2	33,6	4
1436953		M22	22,5	23,5	35,9	4
1436961		M24	24,5	25,5	40	5
1436988		M27	27,5	28,5	43	5
1436996		M30	30,5	31,7	48,2	6